

88882





## SEAMLESS MOBILITY ENGINEERED TO PERFORM

www.jbmbuses.com



JBMÖ

Follow us on:

## **TECHNICAL SPECIFICATION**

## ECO-LIFE

| VEHICLE DESCRIPTION            | 12M LF ELECTRIC CITY BUS   |
|--------------------------------|--|
| Vehicle Dimensions (L x W x H) | 11950 mm X 2550 mm X 3570 mm   |
| Wheel Base                     | 6000 mm  |
| Floor Height                   | 360mm (Full Low Floor)   |
| Seating Capacity               | 35 (2X2) + 1 Driver + 1 Wheel Chair  |
| Passengers Seat Type           | Plastic molded Seats with Cushion & integrated stanchion holder brackets   |
| Driver Seat                    | 4 way adjustable, with 3 point ELR seat belt with seat heater  |
| Front Axle                     | Independent Front Suspension - ZF  |
| Rear Axle                      | Inverted porter axle with Suspension - ZF  |
| Suspension                     | Electronically Controlled Air Suspension System, ECAS  |
| Brakes                         | EBS & ESC, Full Air Brake – WABCO  |
| Kneeling system                | Available  |
| Tyres (Front & Rear)           | Tubeless Radial 275/70 R22.5 X 8.25 Michelin or Equivalent   |
| Structure & Bus Body           | Monocoque body construction in Stainless Steel, Strength & Rollover Requirement as per EU / ECE R 66   |
| Exterior Panels                | Front & Rear FRP , Stretched Steel side panel and Aluminum skirt<br>and roof   |
| Passenger door                 | 3 Nos: Inswing in front and 2 Outswing/Plug type door in middle & rear   |
| Traction Motor                 | Central Motor HV2200-6P ; 250 kW peak  |
| Steering System                | Electric motor driven & Hydraulic power assisted steering with Tilt<br>& telescopic mechanism  |
| Max Speed                      | 70 kmph  |
| Battery Type                   | Advanced Chemistry Li-ion batteries  |
| Regenerative Braking System    | Yes  |
| Charging System                | Dual gun DC Ultra-Fast Charging CCS2 (200A X 2)  |
| HVAC                           | Energy efficient Climate Control with Demister/Defroster. Active filter with antiviral function. Cooling+Heating.  |
| Comfort & Convenience          | Driver Comfort - ADAS, ECAS, EBS; Passenger Comfort - Low floor<br>entry & bus kneeling for easy entry, high performing HVAC, Power<br>ramp for assisting wheelchair |
| HV Safety                      | As per EU norms  |
| Operational Range              | Upto 300 kms (Apx.) - as per e-sort cycle  |

## JBM Electric Vehicles Europe,

Main Airport Center, Unterschweinstiege 2-14, 60549 Frankfurt am Main Call Us: +91-124-4674500 Connect - Mr. Daniel Frade Ph: +49-1721592152